

TECHNICAL DATA SHEET (Preliminary)

Masterbatch series

282 Moo 2 Phraek Sa Mai, Amphoe Mueang Samut Prakan, Samut Prakan 10280, Thailand Tax ID : 0115559016356 Website: Unique-polymer.com

XP-2001 Polymer proccesing aid

Designed to improve extrusion process of polyolefins by coating the inside of die wall to reduce friction between resin and die. Intended to be used for blown film, injection molding, blow molding, pipe and rod extrusion, and profile extrusion. Helps to eliminate melt fracture, increase production output, reduce extruder and die-head pressure, reduce die build up and improve optical properties.

Product description:

XP-2001 contains 2% fluoropolymer content with addition of antioxidants to improve thermal stability. PPA masterbatch appearance is translucent with no tint.

Technical data:

Properties	Value
Polymer carrier	LLDPE
Fluoropolymer content (%)	2
Density (g/cm3)	0.92
MFR 190°C/2.16 kg (g/10min)	6.0
Moisture content (%)	<0.1
Bulk density (g/cm ³)	0.60

Standard packaging:	XP-2001 masterbacthes will be delivered in 25kg PE bags. Other packaging and labelling
	are also available upon request. Product will be arranged on top of wooden pallets for easy handling.
Storage instruction:	Recommended to be used within 18 months of the production date. Product should be

Storage instruction: Recommended to be used within 18 months of the production date. Product should be stored under dry, cool conditions protected from direct sun light. Other storage conditions may impair the quality of the masterbatch.

Declarations:Based on declarations received from our suppliers, materials in this ingredient are in
compliance with international standard regulations such as U.S. FDA 21 CFR 177.1520
and RoHS according to 2002/95/EC.

Revision (DD.MM.YYYY): 28.06.2021

Disclaimer: This information is offered solely for your consideration and verification and should not be construed as a warranty of representation for which Unique Polymer assumes legal liability, except to the extent that such liability is imposed by legislation and cannot be excluded. Values quoted are the results of tests on representative samples and the product supplied may not conform in all respects. Unique Polymer reserves the right to make any improvements or amendments to the composition or any grade or product without alteration to the product code. In using Unique Polymer's products you must establish for yourself the most suitable formulation, production method and control tests to ensure the uniformity and quality of your product is in compliance with all laws.