

TECHNICAL DATA SHEET (Preliminary)

Masterbatch series

282 Moo 2 Phraek Sa Mai, Amphoe Mueang Samut Prakan, Samut Prakan 10280, Thailand Tax ID : 0115559016356 Website: Unique-polymer.com

AS-110 Anti-static masterbatch

Incorporates non-ionic surfactant complexes to help reduce surface resistivity of polyolefin products which can help repel dust or used for electronic packaging. This product is designed to use for films, injection moulded and blow moulded products. Final let down ratio is recommended at 3- 8% depending on thickness and desired surface resistivity.

Product description:	AS-110 contains 10% active ingredient with addition of antioxidants to improve thermal
	stability. Anti-static masterbatches appearance is translucent with no tint.

Technical data:

Properties	Value
Polymer carrier	LLDPE
Additive content (%)	10

Standard packaging: AS-110 masterbacthes will be delivered in 25kg PE bags. Other packaging and labelling are also available upon request. Product will be arranged on top of wooden pallets for easy handling.

Storage instruction:Recommended to be used within 6 months of the production date. Product should be
stored under dry, cool conditions protected from direct sun light. Other storage conditions
may impair the quality of the masterbatch.

Declarations:Based on declarations received from our suppliers, materials in this ingredient are in
compliance with international standard regulations such as U.S. FDA 21 CFR 177.1520
and RoHS according to 2002/95/EC.

Revision (DD.MM.YYYY): 01.02.2022

Disclaimer: This information is offered solely for your consideration and verification and should not be construed as a warranty of representation for which Unique Polymer assumes legal liability, except to the extent that such liability is imposed by legislation and cannot be excluded. Values quoted are the results of tests on representative samples and the product supplied may not conform in all respects. Unique Polymer reserves the right to make any improvements or amendments to the composition or any grade or product without alteration to the product code. In using Unique Polymer's products you must establish for yourself the most suitable formulation, production method and control tests to ensure the uniformity and quality of your product is in compliance with all laws.